

PAT46LWS

15-Ton, Light Weight C-Head Hydraulic Self-Contained, 18V Lithium-Ion

- 2" jaw opening
- Used with P dies; U dies with PUADP1 adapter (sold separately)
- Light weight, scoop style C-head with 355° head rotation
- Overmolded, ergonomic handle
- Improved ergonomic balance
- Includes 2 batteries, charger, and polymer carrying case
- **EP Enhanced Power** labeled tools accept 2.0, 3.0, 4.0, and 5.0Ah Makita batteries

For Use On:

Copper - #8 AWG Str. - 1500 kcmil

Code Cable, Navy Cable, Flexible, Extra Flexible
1/2" - 1" Ground Rods

Terminals, grounding:

to 500 kcmil; YGA, YGHA, YGF

Terminals, uninsulated:

#8 - 1500 kcmil; YA, YA-2N, YA-L, YA-LB, YA-TC,
YA-2LN, YAB-4N, YAV-L, YAV-RS, YA-TC-FX

Terminals, insulated:

#8 - 2/0; YAEV-L, YAEV-H, YAEV-RS, YAEV-RH

Splices:

#8 - 1500 kcmil; YS, YS-T, YS-L, YS-LB, YST,
YSP-T, YGS, YGHS

Taps:

#14 - 1000 kcmil; YH, YCHC
to 4/0 AWG; YC-C

Taps, grounding:

to 500 kcmil; YGHC-C, YGHP-C, YGHR-C

Aluminum - #8 AWG - 1250 kcmil

Code Cables

Terminals: YA-A, AYP, AYPO

Splices: YS-A, YS-AT, YRB

Taps: YFD, YFN, YFO, YFR

ACSR - see Overhead Transmission & Distribution
Sections H & I of the current BURNDY® Master
Catalog



Specifications:

| | |
|---------------------------|---|
| Output Force: | 15 Tons |
| Tool Weight: | 18.9 lbs |
| Size: | 18.00" x 14.00" x 3.00" |
| Die Style: | P and U style (with PUADP1) |
| Jaw Opening: | 2.00" |
| Operating Voltage: | 18 V-DC Lithium-Ion |
| Recharge Time: | 30 minutes (3.0Ah) 45 minutes (5.0Ah) |
| Warranty: | 5 year limited warranty Lifetime warranty on INFINITY DRIVE® 3 year on batteries and charger |

Accessories:

| | |
|------------------------|--------------------------------|
| Catalog Number: | Description: |
| P15K: | Cutter Die, max. diameter 1.2" |
| PUADP1: | U Die Adapter |
| BAT18VLI: | 3.0Ah Li-Ion battery |
| BAT18V5AHLI: | 5.0Ah Li-Ion battery |
| PATCHGRLI: | 120V-AC Charger |
| PATCHGRLLDC: | 12/24V-DC Charger |
| PT208620: | Lanyard |

Variations: (additional variations may be available)

| | |
|------------------------|----------------------------------|
| Catalog Number: | Description: |
| PAT46LWSLI | with 3.0Ah Li-Ion batteries |
| PAT46CLWSLI | with rubber covered head (3.0Ah) |
| PAT46LWSL5 | with 5.0Ah Li-Ion batteries |
| PAT46CLWSL5 | with rubber covered head (5.0Ah) |

See Important Notes on Page N-6.